

PFT SWING L FC-400V

The universal conveying pump for pumping, applying and spraying

For the application of all pumpable lime- and cement-based ready-mixed dry mortars, wet materials, pasty materials and liquid medias. In combination with an air compressor and spraying gun, the PFT SWING L can also be used for the application of cement-based plasters and paints.



TECHNICAL DATA

Part no.	00178415
Conveying capacity	4 - 90 l/min, continuously adjustable
Conveying distance	up to 30 m
Working pressure	max. 30 bar
Rotor / Stator	TWISTER D 6-3
Motor	400 V, 3 Ph, 50 Hz, 6.05 kW, 146 - 458 rpm
Material hopper	plastic
Wheels	2 wheels, 2 castors
Material outflow	DN35 female part
Coupling reduce	DN35 male part DN25 male part
Filling height	600 mm
Hopper content	70 l
Dimensions: L/W/H	1,500/575/660 mm
Total weight	~ 135 kg





400 V



6.05 kW



3 Ph



4-90 l/min

ADVANTAGES AT A GLANCE



- 1** Fits easily under each mixer
- 2** Plastic material hopper – easy cleaning
- Variable conveying output through pump change (D- or R-pump)
- Pump performance continuously adjustable via potentiometer
- Universal filling from buckets or continuous mixers
- Handy and compact
- Fast cleaning and maintenance
- Transport is possible in any estate car without dismantling
- High conveying output and conveying distance



FIELDS OF APPLICATION

- Adhesive and reinforcement mortar
- Finishing coat
- Insulation mortar
- Floor fillers
- Fine filler
- Masonry mortar
- Floor screed up to 60 l/min

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A – 25 m
- Remote control cable with switch – 25 m
- Safety grille, low – required for continuous mixer
- Water/air hose DN12 Geka | Geka – 5 m
- Nozzle DN19 Geka

PART NO.

- 20423920
- 20456929
- 00253076
- 20211100
- 20215700



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SWING L FC-400V – EN/10.22/PFT