


PFT SWING M FC-230V

The smallest conveying pump ideal for pasty filling plasters

The PFT SWING M have an electrical infinitely adjustable 1.5 kW direct drive. You can pump, press and spray liquid, pumpable and solvent-free materials (in buckets) up to a grain size of 3 mm.

TECHNICAL DATA

Part no.	00151992
Conveying capacity	up to 9 l/min, continuously adjustable
Conveying distance	up to 20 m
Working pressure	max. 20 bar
Rotor / Stator	C 4-2
Motor	230 V, 1 Ph, 50 Hz, 1.5 kW, 10 - 204 rpm
Material hopper	plastic
Wheels	2 wheels, 2 castors
Material outflow	DN25 male part
Filling height	540 mm
Hopper content	38 liters
Dimensions: L/W/H	1,150/560/600 mm
Total weight	~ 70 kg



ADVANTAGES AT A GLANCE



- 1** Pump performance continuously adjustable via potentiometer
- Plastic material hopper – easy cleaning
- Cleaning port in the material hopper
- Variable conveying output through pump change (B or C pump)
- Small, light, handy and compact
- Powerful and reliable operation via standard power socket
- Fast cleaning and maintenance
- Transport is possible in any estate car
- Fits easily under each mixer
- Optional: electrical remote control

FIELDS OF APPLICATION

- Lime-cement render < 3 mm
- Adhesive and reinforcement mortar
- Fine filler
- Finishing coat
- Dispersion paint
- Primer Betokontakt

ACCESSORIES

- Extension cable 3 x 2.5 mm², BLU 3-16 A | BLA 2-16 A – 25 m
- Remote control cable with switch – 25 m
- Cover for material hopper
- Water hose/air hose DN12 Geka | Geka – 5 m
- Nozzle DN19 Geka
- Pump unit B 4-2 for SWING M

PART NO.

- 20423420
- 20456929
- 00159323
- 20211100
- 20215700
- 00159064

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpften

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · D-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights and technical modifications reserved. The respective current version applies. Our warranty refers only to the perfect condition of our machines. Figures given in relation to consumption, quantity and design as well as performance data are based on experience and cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always valid. Illustrations may show customized versions, which are not included in the standard scope of delivery. Change, reprint and photomechanical as well as electronic reproduction, also of excerpts, is only permitted with the explicit approval of Knauf PFT GmbH & Co. KG.

PFT SWING M FC-230V – EN/04.23/PFT